

DECLARATION OF PERFORMANCE

N°: DoP-F

Rev. 6 – 31/10/2023

1. Unique identification code of the product type:
DRY- PRESSED CERAMIC TILES, WITH WATER ABSORPTION $E_b \leq 0,5\%$, FOR INTERNAL AND EXTERNAL WALLS AND FLOORINGS.
2. Intended uses:
FOR INTERNAL AND/OR EXTERNAL FLOORINGS, INCLUDING STAIRS, IN BUILDINGS AND INDUSTRIAL FACILITIES AND FOR INTERNAL AND/OR EXTERNAL WALLS IN BUILDINGS AND INDUSTRIAL FACILITIES.
3. Name and contact address of the manufacturer:
**EMILCERAMICA S.r.l. a socio unico
Via GHIAROLA NUOVA, 29 41042 FIORANO M.SE (MO) ITALY**
4. System of AVCP: **SYSTEM 4**
5. Name and identification number of notified laboratory: **NOT APPLICABLE**
6. Declared Performances:


ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	Class A1 _f /A1		EN 14411:2012
Release for dangerous substances, for:	Cadmium	NPD	
	Lead	NPD	
Breaking strength	Thickness ≥ 7,5 mm	≥ 1300 N	
	Thickness < 7,5 mm	≥ 700 N	
Slipperiness	See Annex 1/.....		
Tactility	NPD		
Bond strength/adhesion	NPD		
Thermal Shock Resistance	Pass		
Durability for:			
Internal Uses:	Pass		
External Uses: freeze-thaw resistance	Pass		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Fiorano M.se (MO)
31/10/2023

Luca Gatti
President



Link to the online copy of the declaration of performance: <https://www.emilgroup.it/downloadarea/>

SLIPPERINESS: ANNEX 1 / PROVENZA

Rev. 15 - 11_2023

		DIN 51130 (DE)	BCRA D.M. 236/1989 (ITA)	UNE 41901:2017 EX (ESP)	CEN/TS 16165 Annex B
TEST METHOD USED		Ramp	Tortus	Pendulum	Ramp (Critical angle α_{shod})
Series	Surface	Value / class			
RE-USE	Naturale	R11	≥ 0,40	3	NPD
	Lappato	NPD	≥ 0,40	NPD	NPD
	20 mm	R11	≥ 0,40	3	NPD
W-AGE	Naturale	R10	≥ 0,40	2	NPD
Q-STONE	Naturale	R10	≥ 0,40	2	NPD
IN-ESSENCE	Naturale	R10	≥ 0,40	NPD	NPD
Q-STONE MINIMAL	Naturale	R10	≥ 0,40	2	NPD
ZERODESIGN	Naturale	R10	≥ 0,40	NPD	NPD
DUST	Naturale	R10	≥ 0,40	NPD	NPD
BIANCO D'ITALIA	Old lappato - Full lappato	NPD	NPD	NPD	NPD
GROOVE	Naturale	R10	≥ 0,40	NPD	NPD
	20 mm	R11	≥ 0,40	3	NPD
GESSO	Naturale	R10	≥ 0,40	NPD	NPD
EVO-Q	Naturale	R10	≥ 0,40	NPD	NPD
PROVOAK	Naturale	R10	≥ 0,40	2	NPD
	Antislip - 20 mm	R11	≥ 0,40	3	NPD
KARMAN	20 mm	R11	≥ 0,40	3	NPD
	Naturale	R10	≥ 0,40	NPD	NPD
TERRAQUEA	Terre naturale	R10	≥ 0,40	NPD	NPD
	Terre Tecnica	R11	≥ 0,40	NPD	NPD
	Aquee	NPD	NPD	NPD	NPD
VULCANIKA	Naturale Lavika	R10	≥ 0,40	2	NPD
	Naturale Raku	R9	≥ 0,40	NPD	NPD
EUREKA	Naturale	R10	≥ 0,40	2	NPD
	Tecnica	R11	≥ 0,40	3	NPD
ALTER	Naturale	R10	≥ 0,40	NPD	NPD
EGO	Naturale	R10	≥ 0,40	NPD	NPD
	Tecnica - 20 mm	R11	≥ 0,40	3	NPD
UNIQUE BLEU	Naturale	R10	≥ 0,40	NPD	NPD
	20 mm	R11	≥ 0,40	3	NPD
	Lappato velouté	NPD	NPD	NPD	NPD
UNIQUE TRAVERTINE	Naturale	R10	≥ 0,40	NPD	NPD
	Full lappato	NPD	NPD	NPD	NPD
	Tecnica - 20 mm	R11	≥ 0,40	4	NPD
RE-PLAY CONCRETE	Naturale	R10	≥ 0,40	2	NPD
	Tecnica - 20 mm	R11	≥ 0,40	3	NPD
UNIQUE MARBLE	Silktech	R10	≥ 0,40	2	NPD
	Lappato	NPD	NPD	NPD	NPD
REVIVAL	Silktech	R10	≥ 0,40	2	NPD
	Silktech plus	R11	≥ 0,40	3	NPD
	20 mm	R11	≥ 0,40	3	NPD
SALT STONE	Naturale	R10	≥ 0,40	2	NPD
	Full lappato	NPD	NPD	NPD	NPD
	Tecnica - 20mm	R11	≥ 0,40	3	NPD
UNIQUE INFINITY	Naturale	R10	≥ 0,40	1	NPD
	Anti-slip	R11	≥ 0,40	3	NPD