

DECLARATION OF PERFORMANCE

N°: DoP-F

Rev. 6 – 31/10/2023

1. Unique identification code of the product type:
DRY- PRESSED CERAMIC TILES, WITH WATER ABSORPTION $E_b \leq 0,5\%$, FOR INTERNAL AND EXTERNAL WALLS AND FLOORINGS.
2. Intended uses:
FOR INTERNAL AND/OR EXTERNAL FLOORINGS, INCLUDING STAIRS, IN BUILDINGS AND INDUSTRIAL FACILITIES AND FOR INTERNAL AND/OR EXTERNAL WALLS IN BUILDINGS AND INDUSTRIAL FACILITIES.
3. Name and contact address of the manufacturer:
**EMILCERAMICA S.r.l. a socio unico
Via GHIAROLA NUOVA, 29 41042 FIORANO M.SE (MO) ITALY**
4. System of AVCP: **SYSTEM 4**
5. Name and identification number of notified laboratory: **NOT APPLICABLE**
6. Declared Performances:


| ESSENTIAL CHARACTERISTICS | PERFORMANCE | | HARMONISED TECHNICAL SPECIFICATION |
|---|----------------------------|---------------|------------------------------------|
| Reaction to fire | Class A1 _{fl} /A1 | | EN 14411:2012 |
| Release for dangerous substances, for: | Cadmium | NPD | |
| | Lead | NPD | |
| Breaking strength | Thickness $\geq 7,5$ mm | ≥ 1300 N | |
| | Thickness $< 7,5$ mm | ≥ 700 N | |
| Slipperiness | See Annex 1/..... | | |
| Tactility | NPD | | |
| Bond strength/adhesion | NPD | | |
| Thermal Shock Resistance | Pass | | |
| Durability for: | | | |
| Internal Uses: | Pass | | |
| External Uses: freeze-thaw resistance | Pass | | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Fiorano M.se (MO)
31/10/2023

Luca Gatti
President



Link to the online copy of the declaration of performance: <https://www.emilgroup.it/downloadarea/>

SLIPPERINNES: ANNEX 1 / VIVA
Rev. 11 - 11/2023

| | | DIN 51130 (DE) | BCRA D.M. 236/1989 (ITA) | UNE 41901:2017 EX (ESP) | CEN/TS 16165 Annex B |
|------------------|--------------------------------|----------------------|--------------------------------|-------------------------|---|
| TEST METHOD USED | | Ramp | Tortus | Pendulum | Ramp (Critical angle α_{shod}) |
| Series | Surface | Value / class | | | |
| NR.21 | Naturale | R10 | $\geq 0,40$ | 2 | NPD |
| STATALE 9 | Naturale | R11 | $\geq 0,40$ | 2 | NPD |
| ACUSTICO 12 | Naturale | R10 | $\geq 0,40$ | 2 | NPD |
| 99 VOLTE | Naturale | R10 | $\geq 0,40$ | NPD | NPD |
| TERZO TEMPO | Naturale | R10 | $\geq 0,40$ | NPD | NPD |
| | Antislip | R11 | $\geq 0,40$ | NPD | NPD |
| "+3" | Naturale | R10 | $\geq 0,40$ | NPD | NPD |
| | Antislip - 20 mm | R11 | $\geq 0,40$ | 3 | NPD |
| | Lappato | NPD | NPD | NPD | NPD |
| 300° | Naturale | R10 | $\geq 0,40$ | 2 | NPD |
| L'H | Naturale | R9 | $\geq 0,40$ | NPD | NPD |
| NO CODE | Laccato - Cerato | R9 | $\geq 0,40$ | NPD | NPD |
| | Tecnica | R11 | $\geq 0,40$ | 3 | NPD |
| DOTCOM | Naturale | R10 | $\geq 0,40$ | 2 | NPD |
| YAKI | Naturale | R9 | $\geq 0,40$ | NPD | NPD |
| HERITAGE | Naturale | R10 | $\geq 0,40$ | NPD | NPD |
| | 20 mm | R11 | $\geq 0,40$ | 3 | NPD |
| NARCISO | Naturale | R10 | $\geq 0,40$ | NPD | NPD |
| | Full lappato - Lappato matt | NPD | NPD | NPD | NPD |
| METALLICA | Naturale | R10 | $\geq 0,40$ | NPD | NPD |
| | Slabs (120x278) | R9 | $\geq 0,40$ | NPD | NPD |
| | Metalbrick | NPD | NPD | NPD | NPD |